

| | DIGI-Compact | DIGI-Compact HC | DIGI-5 | DIGI-7 |
|--|--------------------|--------------------|--------------------|--------------------|
| Offline or online printing possible | Yes | Yes | Yes | Yes |
| Single Pass System | Yes | Yes | Yes | Yes |
| Manual Loading | Yes | Yes | Yes | Yes |
| Pick & Place / Robot automatic loading | optional | optional | optional | optional |
| Plasma / Flame / Pyrosil / Corona / Ionization / NIR | optional | optional | optional | optional |
| UV Mercury and/or UV LED end curing included | Yes | Yes | Yes | Yes |
| Resolution / DPI (dots per inch) | 360 | 360 | 360 | 360 |
| Maximum numbers of colors | 6 | 6 | 10 | 10 |
| Maximum numbers of UV LED units | 5 | 5 | 10 | 10 |
| Remote diagnostics available | Yes | Yes | Yes | Yes |
| OPC UA - Connection | Yes | Yes | Yes | Yes |
| TCP/IP - Connection | Yes | Yes | Yes | Yes |
| User friendly HMI with touch screen | Yes | Yes | Yes | Yes |
| Mist absorption | Yes | Yes | Yes | Yes |
| Capacity of carriers per hour (*) | 120-175 | 240-350 | 50-80 | 500-800 |
| Internal exhaust system with filters | Yes | Yes | Yes | Yes |
| Max carrier length mm | 600 | 600 | 800 | 800 |
| Max carrier width mm | 200 | 200 | 300 | 300 |
| Max product height mm | 200 | 200 | 200 | 200 |
| Printing width mm | 70 | 70 | 70 / 140 / 210 | 70 / 140 / 210 |
| Power Connection | 3 x 400V+N+Pe | 3 x 400V+N+Pe | 3 x 400V+N+Pe | 3 x 400V+N+Pe |
| Size printer L x W x H in mm approx. (**) | 3200 x 1800 x 2420 | 3200 x 1800 x 2420 | 5490 x 1800 x 2420 | 5490 x 1800 x 2420 |
| Size printer L x W x H with open doors in mm app. | 3200 x 1800 x 2700 | 3200 x 1800 x 2700 | 5490 x 1800 x 2700 | 5490 x 1800 x 2700 |
| Weight of printer (approx.) | 2.000 kg | 2.000 kg | 4.500 kg | 4.500 kg |
| Air Connection | 6 bar | 6 bar | 6 bar | 6 bar |

(*) depending on print speed and lay-out
(**) excl. transport belt